

SAFETY DATA SHEET

According to EC 1907/2006 (REACH)

Date last verification

: 2015-01-30

: 2012-07-21

Revision date
Publication date

: 2005-06-17

Version number: 2.1

Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SDS

: 22606

Product code 12nc

: 9898 031 50161

Supplier

: MICRO POWER ELECTRONICS, INC.

13955 SW Millikan Way OR 97005 Beaverton

Oregon

United States of America TEL:+1 503-693-7600 FAX:+1 503-648-9625

Tradename

: FR3 LIMNO2 BATTERY (989803150161) (453564288012) : LITHIUM METAL BATTERIES [6.72 G

LITHIUM]

1.2. Relevant identified uses of the substance or mixture and uses advised against

General description

: BATTERY

Use

: Various

Uses advised against

: Data not available.

1.3. Details of the supplier of the safety data sheet

Supplier safety data sheet

: Philips Electronics Nederland B.V., P.O. Box 218, 5600 MD Eindhoven, Tel. +31 (0)40 2747588

Responsible department

: dangerous.goods@philips.com

1.4. Emergency telephone number

Emergency telephone number

: +31 (0)497-598315

2. Hazards identification

2.1. Classification of the substance or mixture

GHS: (EC) No 1272/2008

Not classified according to GHS classification.

EC: (EC) No 67/548 or 1999/45

Not classified according to EC classification.

2.2. Label elements

GHS: (EC) No 1272/2008

GHS-Label: not applicable

Remarks on GHS-labelling

none

EC: (EC) No 67/548 or 1999/45

EC-Label: not applicable

Remarks on EC-labelling

none

2.3. Other hazards

Data not available.

Date of request : 2015-10-01 SDS 22606 - Page 1 / 8

Composition/information c	an Ingresitems	514			
Component	CAS-no. EC-no.	Index No. Registration no.	— Percentage(%)	GHS-Label EC-Label	
LITHIUM	7439-93-2 231-102-5	003-001-00-4 01-2119966143-38		GHS02 GHS05 H260 Water-react. 1 H314 Skin corr. 1B EUH014 F,C;R: 14/15 34	
MANGANESE DIOXIDE	1313-13-9 215-202-6	025-001-00-3 01-2119452801-43		GHS07 GHS08 H302	
LITHIUM TRIFLUOROMETHANESULPHONATE	33454-82-9 251-528-5			GHS07 H315 Skin irrit. 2 H319 Eye irrit. 2 H335 STOT SE 3 Xi;R: 36/37/38	
PROPYLENE CARBONATE	108-32-7 203-572-1	607-194-00-1 01-2119537232-48		GHS07 H319 Eye irrit. 2 Xi;R: 36	
DIMETHOXYETHANE, 1,2-	110-71-4 203-794-9	603-031-00-3 01-2119485981-24		GHS02 GHS07 GHS08 H225 Flam. liq. 2 H332 Acute tox. 4 H360FD Repr. 1B EUH019 F,T;R: 60 61 11 19 20 Repr.Cat. 2	

For the full text of the H-sentences, hazard statements and R-sentences mentioned in this section, see section 16.

4. First aid measures

4.1. Description of first aid measures

Skin : Not applicable. Ingestion : Not applicable.

Inhalation: Not applicable.Eyes: Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Skin local : Not applicable. Not applicable. general Ingestion local : Not applicable. general : Not applicable, Inhalation Not applicable. local Not applicable. general local : Not applicable.

Remarks symptoms : None

4.3. Indication of any immediate medical attention and special treatment needed

None

5. Firefighting measures

5.1. Extinguishing media

Suitable fire-extinguisher

determined by surrounding

Unsuitable fire-extinguisher

not traceable

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in fire : lithium oxide, manganese oxides, carbon monoxide, hydrogen fluoride, sulphur oxides

5.3. Advice for firefighters

In the event of fire, wear protective clothing and use breathing apparatus that is independent of the ambient air.

5. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Precautions

Use protective equipment. See section 8.

Emergency procedure

Is not to be expected.

6.2. Environmental precautions

Remainder material has to be incinerated in_a proper installation or dumped on an approved landfill, in accordance with local and national legislation.

6.3. Methods and material for containment and cleaning up

Spillage procedure

not applicable

6.4. Reference to other sections

See section 8 for appropriate personal protection.

See section 13 for additional information on waste treatment.

7. Handling and storage

7.1. Precautions for safe handling

Observe label precautions.

Do not eat, drink or smoke in work areas. Remove contaminated clothing and protective equipment. Wash hands after leaving the work area.

Local exhausting

: Under normal circumstances not applicable.

Storage code (on behalf of PGS: M4

15)

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

See also any precautionary statements and S-phrases in section 2.2.
 Store product protected from proximity to other sources of heat, dry.

7.3. Specific end use(s)

Data not available.

8. Exposure controls/personal protection

8.1. Control parameters

Exposure limits :

Date of request : 2015-10-01 SDS 22606 - Page 3 / 8

applicable to: The Netherlands (20 °C; 1013 mbar)

No TWA has been laid down.

TWA(8 hours): 1 mg/m3 MANGANESE DIOXIDE(as manganese)
TWA(15 minutes): 3 mg/m3 MANGANESE DIOXIDE(as manganese)
No TWA has been laid down. LITHIUM TRIFLUOROMETHANESULPHONATE

No TWA has been laid down. PROPYLENE CARBONATE
No TWA has been laid down. DIMETHOXYETHANE, 1,2-

applicable to: Belgium (20 °C; 1013 mbar)

TWA(8 hours): 0.2 mg/m3 MANGANESE DIOXIDE(as manganese)

applicable to: Germany (20 °C; 1013 mbar)

TWA(8 hours): 0.5 mg/m3 MANGANESE DIOXIDE(as manganese, inhalable dust)

applicable to: United States of America (25 °C; 1013 mbar)

TWA(8 hours): 0.02 mg/m3 MANGANESE DIOXIDE(as manganese, respirable dust) -

[according to ACGIH]

TWA(8 hours): 0.1 mg/m3 MANGANESE DIOXIDE(as manganese, inhalable dust) -

[according to ACGIH

TWA(8 hours): 5 mg/m3 C MANGANESE DIOXIDE(as manganese) - [according to

OSHA]

applicable to: Sweden (20 °C; 1013 mbar)

TWA(8 hours): 0.02 mg/m3 C LITHIUM(as inhalable dust)

 TWA(8 hours):
 0.2 mg/m3
 MANGANESE DIOXIDE(as manganese, dust)

 TWA(8 hours):
 0.1 mg/m3
 MANGANESE DIOXIDE(as manganese, respirable dust)

 TWA(8 hours):
 0.02 mg/m3
 C
 LITHIUM TRIFLUOROMETHANESULPHONATE(as

lithium, inhalable dust)

applicable to: Switzerland (20 °C; 1013 mbar)

TWA(8 hours): 0.5 mg/m3 MANGANESE DIOXIDE(as manganese, inhalable dust)

applicable to: China (20 °C; 1013 mbar)

TWA(8 hours): 0.15 mg/m3 MANGANESE DIOXIDE

C=Ceiling; S=Skin

Remarks exposure limits :

none

DNEL (Derived No Effect Level)

Data not available.

PNEC (Predicted No Effect Concentration)

Data not available.

8.2. Exposure controls

Advised personal protection:

Hands : not applicable
Breakthrough time : not applicable
Eyes : not applicable
Inhalation : not applicable

Skin : none (when used normally)

Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : battery

Colour : type dependent
Odour : odourless
Odour threshold (20°C; 1013 mbar) : not traceable
pH : not applicable

Melting point/range : not traceable Boiling point/range : not traceable Flash point/range not applicable Vapor rate/range not applicable Flammability (solid, gas) : data not available **Explosive limits** : not applicable Vapour pressure : not applicable Density : not traceable Solubility in water not applicable

Log Po/w : <0 MANGANESE DIOXIDE Source : [UCLID

-0.49 LITHIUM TRIFLUOROMETHANESULPHONATE Source : Easi View
-0.48 PROPYLENE CARBONATE Source : IUCLID

Date of request : 2015-10-01 SDS 22606 - Page 4 / 8

-0.21

DIMETHOXYETHANE, 1,2-

: ChemDat (Merck) Source

Autoignition temperature Decomposition temperature

: not applicable : not traceable : not applicable

Dust explosions possible in air

: not applicable

Oxidising properties

Viscosity

: no

9.2. Other information

Solubility in fat Electrostatic chargement : not applicable not traceable

Stability and reactivity

10.1. Reactivity

See section 10.2 - 10.6.

10.2. Chemical stability

The substance or mixture is stable under normal conditions. See also section 10.4.

Possibility of hazardous reactions

Reactions with water

Other hazardous conditions

: Data not available.

Conditions to avoid

Data not available.

10.5. Incompatible materials

Hazardous reactions with

none

Hazardous decomposition products

Hazardous decomposition products at heating : none

Toxicological information

Information on toxicological effects

LD-50: >3.478 g/kg (ORL-RAT)	MANGANESE DIOXIDE	Source	: ChemDat (Merck)
LD-50: 29 g/kg (ORL-RAT)	PROPYLENE CARBONATE	Source	: IUCLID
LD-50: 5.37 mg/kg (ORL-RAT)	DIMETHOXYETHANE, 1,2-	Source	: ChemDat (Merck)
LD-50: 3.2 g/kg (ORL-MUS)	DIMETHOXYETHANE, 1,2-	Source	: Sigma-Aldrich

Acute dermal toxicity

LD-50: >5 g/kg (SKN-RAT) : ChemDat (Merck) DIMETHOXYETHANE, 1,2-Source

Acute inhalation toxicity

There are no data available.

Ames test

negative PROPYLENE CARBONATE Source : IUCLID negative : ChemDat (Merck) DIMETHOXYETHANE, 1,2-Source

Skin corrosion/irritation

The substance or mixture is not classified for skin corrosion/-irritation.

Serious eye damage/irritation

The substance or mixture is not classified for serious eye damage/irritation.

Respiratory or skin sensitisation

The substance or mixture is not classified for respiratory or skin sensitisation.

Germ cell mutagenicity

The substance or mixture is not classified for germ cell mutagenicity.

Carcinogenicity

The substance or mixture is not classified for carcinogenicity.

Reproductive toxicity

The substance or mixture is not classified for reproductive toxicity.

Specific target organ toxicity-single exposure

The substance or mixture is not classified for specific target organ toxicity-single exposure.

Specific target organ toxicity-repeated exposure

The substance or mixture is not classified for specific target organ toxicity-repeated exposure.

Aspiration hazard

The substance or mixture is not classified for aspiration hazard.

Symptoms

Not applicable. local general Not applicable. Ingestion local Not applicable. general Not applicable. Inhalation Not applicable. local general Not applicable. Eyes local Not applicable.

Remarks symptoms : None

12. Ecological information

12.1. Toxicity

Ecotoxicity

LC-50: 5300 mg/l/96H (Fish)	PROPYLENE CARBONATE	Source : IUCLID
EC-50: >500 mg/l/48H (Daphnia)	PROPYLENE CARBONATE	Source : IUCLID
IC-50: >500 mg/l/72H (Algae)	PROPYLENE CARBONATE	Source : IUCLID
LC-50: >500 mg/l/96H (Fish)	DIMETHOXYETHANE, 1,2-	Source : ACROS

12.2. Persistence and degradability

Biological oxygen demand (5)	: 0.025 g/g	PROPYLENE CARBONATE	Source	: IUCLID
Chemical oxygen demand	: 1.29 g/g	PROPYLENE CARBONATE	Source	: IUCLID
Biological(5)/chemical oxygen	: 0.019	PROPYLENE CARBONATE		

demand ratio

 Degradability
 : not
 MANGANESE DIOXIDE
 Source
 : ACROS

 readily
 PROPYLENE CARBONATE
 Source
 : IUCLID

12.3. Bioaccumulative potential

Log Po/w	:	<0	MANGANESE DIOXIDE	Source	:	IUCLID
		-0.49	LITHIUM TRIELUOROMETHANESULPHONATE	Source		Easi View
		-0.48	PROPYLENE CARBONATE	Source	:	IUCLID
		-0.21	DIMETHOXYETHANE, 1,2-	Source	:	ChemDat (Merck)

12.4. Mobility in soil

Biochemical factor

Henry Constant	: 9.92E-8 atm m3/mol	LITHIUM TRIFLUOROMETHANESULPHONATE	Source	: Easi View
	3.63E-4 atm m3/mol	PROPYLENE CARBONATE	Source	: Easi View

12.5. Results of PBT and vPvB assessment

: not traceable

Data not available.

12.6. Other adverse effects

Remarks on ecotoxicity : none

Disposal considerations

13.1. Waste treatment methods

Remainder material has to be incinerated in_a proper installation or dumped on an approved landfill, in accordance with local and national legislation.

Date of request: 2015-10-01 SDS 22606 - Page 6 / 8

Transport information

UN number 14.1.

ADR/RID IMDG/IMO 3090 3090 3090

Remarks IATA/ICAO

: The product must be transported in accordance with the regulations of IATA PACKING INSTRUCTION 968 - SECTION IA (Meets the GENERAL REQUIREMENTS of IATA PACKING INSTRUCTION 968). The batteries meet the requirements of each test of the "UN Manual of Tests and Criteria, Part III,

SDS 22606 - Page 7 / 8

subsection 38.3".

UN proper shipping name 14.2.

ADR/RID IMDG/IMO

IATA/ICAO

: LITHIUM METAL BATTERIES : LITHIUM METAL BATTERIES

IATA/ICAO

: LITHIUM METAL BATTERIES

14.3. Transport hazard class(es)

ADR/RID: 9

IMDG/IMO: 9

IATA/ICAO: 9

14.4. Packing group

ADR/RID : none

IMDG/IMO: none

IATA/ICAO : none

Environmental hazards 14.5.

Marine pollutant

: no

14.6. Special precautions for user

Hazard identification number (ADR/RID)

: none

EmS (IMDG/IMO)

: F-A, S-I

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Data not available.

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

- Data not available.

Chemical safety assessment

Data not available.

Other information

Remarks on SDS

: The presence of lithium-batteries gives an enlarged risk of fire.

Overview relevant H-sentences from all components in section 3

H225 Highly flammable liquid and vapour.

H260 In contact with water releases flammable gases which may ignite spontaneously.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage. H315

Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H360FD May damage fertility. May damage the unborn child.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

Reacts violently with water. EUH014 **EUH019** May form explosive peroxides.

Overview relevant hazard statements from all components in section 3

C CORROSIVE

F HIGHLY FLAMMABLE

T TOXIC
Xi IRRITANT
Xn HARMFUL

Overview relevant R-sentences from all components in section 3

11 Highly flammable.

14/15 Reacts violently with water, liberating extremely flammable gases.

19 May form explosive peroxides.

20 Harmful by inhalation.

20/22 Harmful by inhalation and if swallowed.

34 Causes burns.36 Irritating to eyes.

36/37/38 Irritating to eyes, respiratory system and skin.

60 May impair fertility.

61 May cause harm to the unborn child. 62 Possible risk of impaired fertility.

63 Possible risk of harm to the unborn child.

Training advice

Provide adequate information, instruction and training for operators.

A key or legend to abbreviations and acronyms used in the safety data sheet

REACH Registration, Evaluation and Authorisation of CHemicals

GHS Globally Harmonised System of Classification and Labelling of Chemicals

CAS Chemical Abstracts Service
TGG = TWA Time Weighted Average
LEL Lower Explosive Limit
UEL Upper Explosive Limit

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route RID Règlement concernant le transport international ferroviaire des marchandises dangereuses

UN United Nations

 IMDG
 International Maritime Dangerous Goods

 IMO
 International Maritime Organization

 IATA
 International Air Transport Association

 ICAO
 International Civil Aviation Organization

EmS Emergency Schedule

Date of request: 2015-10-01 SDS 22606 - Page 8 / 8

^{*} Point to alterations with regard to the previous version.

The information provided in this Material Safety Data Sheet is correct to the best of the knowledge, information and belief of Philips Electronics Nederland B.V. at the date of its printing.